

Ultra High Frequency Tag



UHF1-Tag2

UHF1-Tag2 adopts ultra high frequency encrypted chip, especially designed for ZK UHF reader. This tag is ultra thin electronic tag, easy to stick to the surface of objects, and has a long reading distance, a good choice to be applied in personnel management.

Features

- High Safety
- High Reading Rate

- High Chip Sensitivity
- Flexible Storage Structure

Typical Applications

- Other Special Management
- Near-range Non-contact Identification
- Data Informatization Intelligent System Application

Specifications

Model	UHF1-Tag2
Working Frequency	860~928MHz
Reading Distance	Up to 10 meters for UHF1-10E and UHF1-10F (Determined by the environment and reader)
Protocol	ISO18000-6C
Memory Capacity	800 bits
Chip UID	64 bytes
Storage Structure	EPC: 96 bits; TID :96 bits; User: 512 bits; Password: 64 bits
Data Storage	5 years (Only for chip)
Working Temperature	-30°C ~ 75°C
Storage Temperature	-10 °C ~ 40 °C
Storage Humidity	40%-50% RH
Dimension	72mm*20mm (error±0.02mm)
Packaging Process	Overlay

Notes

- 1.In order to get the best recognition performance, please keep the tag direction the same as antenna's polarization direction when using (Remarks: You should hold the card horizontally when swiping it).
- 2. The working temperature must be within the allowable range, otherwise it may cause the product to work abnormally.
- 3. The storage temperature and humidity must be within the allowable range, otherwise it will reduce the service life of the product.
- 4. The distance from the product 30mm should not have an electric field or a strong current through, which may cause interference to the product.
- 5.The distance from the product 30mm should not have metal objects, which may cause the product to work abnormally.
- 6. The product should be kept away from the magnetic field for storage to prevent data loss.

